

Video Presentation Stand

VID-P50



Simple and Easy to Use-With All of the Features That You Need to Present Clear, Sharp, Professional Images

Video presentation stands have become a powerful imaging tool for business professionals and educators. Whether presenting a new business plan, lesson plan or providing legal documentation, using the Sony VID-P50 Video Presentation Stand will assist you in adding a dynamic visual element to your presentation. Incorporating outstanding features including high horizontal resolution and a 12 times powered zoom lens, the Sony VID-P50 delivers high quality images and yet remains cost-effective.

Because of its simple operation, anyone can use the VID-P50 to enrich their presentations. The VID-P50 is a good choice for the boardroom, classroom or courtroom. Its basic design makes it compact and portable for busy people on the go.

Features

- Clear image reproduction with a high horizontal resolution of over 460TV lines for NTSC and over 450TV lines for PAL model
- 12 times powered zoom capability
 Two zooming speeds (fast/slow)
- Fully automatic functions for easy operation

 Auto Focus

 Auto Iris


 Auto White Balance
- Lighting unit as standard
- Flip up and tilt camera head up to 90 degrees to capture images within the room
- One-touch detachable close-up lens

- Video output and S-video (Y/C) output connector
- Document area is (300 × 300) enabling the use of A4 or letter size documents or other presentation materials
- Light weight, easy-to-carry design



Applications

Business



Video Conferencing

Education



Distance Learning



Specification

Color system: NTSC/PAL color system

Pickup device: 1/3-inch Interline-transfer CCD×1

Picture element: 768 (H) × 494 (V) (NTSC)

752(H)×582(V) (PAL)

Resolution: More than 460TV lines (horizontal) (NTSC)

More than 450TV lines (horizontal) (PAL)

S/N ratio: More than 48dB

Lens: F1.8 f=5.4~64.8mm (×12 power zoom)

Shooting area: 300×225mm (WIDE)

(11 ⁷/₈ × 10 ¹/₈ inches) 25 × 19mm (TELE) (1 × ³/₄ inches)

Focus: Full Auto Iris: Full Auto

Lighting: 4W fluorescent lamp×1

White balance: Full Auto

Outputs: Video (Phono connector×1)

1Vp-p sync negative S-video (4pin mini DIN×1)

Y: 1Vp-p, 75Ω sync negative C: 0.286Vp-p, 75Ω (NTSC)

C: 0.300Vp-p, 75Ω (PAL)

Dimensions: 335(W)×525(H)×355(D) mm (131/4×203/4×14 inches)

<when folded>

335 (W)×70 (H)×550 (D) mm (13 1/4 × 2 7/8 × 21 3/4 inches)

Mass: 4.1kg (9lb 1oz)

Power requirement: AC 120V 60Hz 150mA AC 230V 50/60Hz 10W



rear view

Distributed by

Features and specifications subject to change without notice.